

PRODUCT DATA SHEET



	DIMENSIONS	WATERPROOF CORE PANEL WEIGHT
SQUARE CUT PANEL SIZE	2440 x 900 x 10.5mm	20kg
SQUARE CUT PANEL SIZE	2440 x 1200 x 10.5mm	27kg
PROCLICK PANELS	2440 x 579 x 10.5mm	13kg
PROCLICK PANELS	2440 x 879 x 10.5mm	20kg
PROCLICK PANELS	2440 x 1179 x 10.5mm	27kg

DIMENSION TOLERANCE

WIDTH	+/- 3.0mm
HEIGHT	+/- 5.0mm
THICKNESS	+/- 0.5mm
FLATNESS	≤3mm/m
SQUARENESS	+/- 1.5mm per 1000mm

MATERIAL

Face laminates are produced to EN 438 standard (VGS) and are bonded to a quality exterior grade MDF, or Plywood using a D3 adhesive applied under strictly controlled conditions. A balancing backing laminate is then bonded to the panel reverse.

FIRE RATINGS / PERFORMANCE

All Crosswater panels are classified EN 13501. In addition, selected decors are British Standard Fire Rated Class 2-BS 476 : Part 7 : 1997. Please check with your Crosswater supplier or retailer for confirmation of any particular decors F.R status prior to purchase, if required.

GUARANTEE

30 year warranty against manufacturing defects in a domestic environment (subject to installation registration), and 5 years when installed in a commercial environment.

PRODUCT CODES

CW05WPCP12	CW06WPCP12	CW07WPCP12
CW08WPCP12	CW05WPCS12	CW06WPCS12
CW07WPCS12	CW08WPCS12	CW09WPCP12
CW09WPCS12	CW10WPCP12	CW10WPCP12
CW11WPCP12	CW12WPCP12	CW13WPCP12
CW14WPCP12	CW10WPCS12	CW11WPCS12
CW12WPCS12	CW13WPCS12	CW14WPCS12
CW05WPCP60	CW06WPCP60	CW07WPCP60
CW08WPCP60	CW09WPCP60	CW10WPCP60
CW11WPCP60	CW12WPCP60	CW13WPCP60
CW14WPCP60	CW05WPCP90	CW06WPCP90
CW07WPCP90	CW08WPCP90	CW05WPCS90
CW06WPCS90	CW07WPCS90	CW07WPCS90
CW09WPCP90	CW09WPCS90	CW10WPCP90
CW11WPCP90	CW12WPCP90	CW13WPCP90
CW14WPCP90	CW10WPCS90	CW11WPCS90
CW12WPCS90	CW13WPCS90	CW14WPCS90

RANGE

Laminate Panels

DESCRIPTION

Crosswater laminate wall panel collection

CARE & MAINTENANCE

DO	Regularly use non-abrasive cleaner to clean the panels.
	Replace any exposed silicone sealant periodically, or as necessary, to ensure a continual waterproof seal.
	Rinse your Crosswater panels down after use as a multitude of various chemicals can be present within personal hygiene products used in bathrooms. Rinsing these off, avoids issues such as sealant discolouration.
	Ensure adequate ventilation is present when using your shower or bath to avoid mould and mildew growth occurring.
DON'T	Use any form of abrasive cleaner as these may result in dulling of your panel surface and accelerated wear affects.
	Use any form of bleach product to clean your Crosswater panels as harsh chemicals contained in bleaches can affect the surface of your panel and sealant.

DISCLAIMER

Be aware that gloss finished decors have a lower scratch resistance than textured decors and that the stated care & maintenance procedures must be followed to minimise normal wear and tear of the products.