Optix 10 Pivot Door

IMPORTANT

BEFORE STARTING THE INSTALLATION ENSURE ALL THE DOOR SIZE MEASUREMENTS CORRESPOND WITH THE INSTALLATION AREA INCLUNDING THE FINISHED TILED/PANELLED WALLS. RETURNS DUE TO INCORRECT SIZING WILL NOT BE ACCEPTED.

OXWPSC0800	47Kgs
OXWPSC0900	53Kgs
OXWPFC0800	47Kgs
OXWPFC0900	53Kgs
OXWPVC0800	47Kgs
OXWPVC0900	53Kgs



Manufactured to: BS EN 14428

OXWPSPSC0800	47Kgs
OXWPSPSC0900	52Kgs
OXWPSPFC0800	47Kgs
OXWPSPFC0900	52Kgs
OXWPSPVC0800	47Kgs
OXWPSPVC0900	52Kgs



Optix 10 Pivot Door

Optix 10 Side Panel for Pivot Door





IMPORTANT - Please read before installation

Please read these instructions carefully before starting installation and keep in a safe place for future reference.

Check the contents of the pack carefully before installation. Crosswater will not be held responsible for any de-fit / re-fit costs where faulty product has been fitted.

If any fault is found with materials or workmanship, it must be reported immediately to the manufacturer. Remedial action will be taken, based on information received, on condition that:

- 1. Full details are supplied to the manufacturer;
- The enclosure has not been modified or tampered with;
 The manufacturer is informed of any damage/shortages prior to installation.

We do not accept responsibility for any problems that may occur through incorrect installation.

The success of the installation and operation of any shower enclosure is, of course, dependant on the squareness, alignment and construction of the walls to which fixing is to be carried out.

INSTALLATION - Advise and safety

The installation instructions are based on typical use and conditions.

All doors are designed to open outwards only.

These hints have been prepared for your guidance, you must exercise due care at all times.

For Health and Safety 2 people must carry out the installation of this enclosure.

Handle glass with care. Although the glass supplied is toughened safety glass(**EN12150**), impacts can damage both the glass and the frame.

CARE AND CLEANING

Do not use solvents or abrasive material or chemicals to clean the enclosure.

INSTALLATION - Left and Right hand

Only clean using soapy water and soft cloth, rinse thoroughly afterwards.

This product is reversible for left or right hand opening. Please follow the diagram, and detail below for your choice of installation.









VERY IMPORTANT

You must complete all tiling and grouting, and the shower tray **MUST** be level and fully sealed to the tiles before installation. If you do not fit the enclosure onto a tiled surface, or seal the tiles to the tray before installation, water may soak into the wall behind the wall profiles.



Warning! Please chec

Please check for any hidden pipes or cables before drilling holes in the wall.

When using power tools always follow the manufacturers user instructions.

If the Framework is sealed to the tray on the inside, any water that may get into the framework will not be able to drain back into the tray, this may cause the enclosure to leak.

Leave the silicone sealant to dry for 24 hours before using the enclosure.







Installation tool

Step A1



















Step A4





Α



6

B = B



Step A8



Step A9













Step A10



Α



×°



Step B1







Α

Crosswater SHOWERING

Step B3





Step B5



Step B6



x1

B2 x1



Step B7







Step B8





Step B9



Step B10







For any further information please contact Crosswater Phone number, 0345 873 8840 Website, www.crosswater.co.uk Email address, sales@crosswater.co.uk The manufacturer reserves the right to make technical modifications without prior notice.